

FRAME SCREENS

FLAT ELASTIC


from 160 cm. to 400 cm. widths



FLAT ELASTIC are the right solutions for the installer who needs a frame screen either for rear or for front projection.

They bring together high quality standards with a good versatility.

Available 1:1, 4:3, 16:9 and 16:10 formats or **bespoke sizes**.



4:3 Ratio

Viewing area

(WxH)

160 x 120

180 x 135

200 x 150

220 x 165

250 x 190

300 x 225

350 x 265

400 x 300

TECHNICAL SPECIFICATIONS

- Smart design and easy to install
- Aluminium frame painted with dull black epoxy powders (RAL 9005 and plastic joint corners for SAFETY reasons*
- On request the corners can be of aluminium cut at 45°
- Frame dimensions: 80x20 mm. (WxD)
- Flat elastic: projection surface anchoring system is with galvanized rods and rubber bands
- Flat press: projection surface anchoring system is with press stud buttons
- Wall mounting brackets on upper and lower frame for safe installation - Flame-retardant projection surfaces
- * Standard aluminium corners cut at 45° on screens bigger than 300 cm. of width.





Wall bracket

Flat Elastic anchoring system

PROJECTION CLOTHS			
Front projection surfaces	Gain	Rear projection surfaces	Gain
White	1.2	Rear Plus	1.1
HD Performer	1.3	Rear Lux R114	2.5
Lumi Grey	0.8	Front Rear	0.9
Cinesound*	0.7		
Microperforated	1.1		
Lumi Grey Microperforated	0.8		
Foldaway*	1.5		
Fibre Matte*	1.25		
Pure KS	1.1		
Pure Matte KS	1.1		
Silver Blast*	1.3		
Bright Contrast 3D 0.8*	0.8		
Green Screen			
*Limited in height			

The measures in the drawings are expressed in millimetres.

1:1 Ratio

Viewing area

(WxH)

160 x 160

180 x 180

200 x 200

220 x 220

250 x 250

300 x 300

_



Warranty: 24 months

DIMENSIONS measures in cm

16:10 Ratio

Viewing area

(WxH)

160 x 100

180 x 112

200 x 125

220 x 137

250 x 156

300 x 187

350 x 219

400 x 250

16:9 Ratio

Viewing area

(WxH)

160 x 90

180 x 101

200 x 112

220 x 124

250 x 140

300 x 169

350 x 197

400 x 225

Approx. net

weight

(Kg)

11

13

14

16

19

23

27

31