

LOW VOLTAGE CONTACT INTERFACE

The **LOW VOLTAGE CONTACT INTERFACE** can be used to control an electric screen or projector lift by low voltage contact closures and/or via permanent switcher.

- Power supply 230V a.c.± 10% 50Hz
- Maximum output current 10Acosφ1,4Acosφ 0.4
- Output voltage on contacts 5/6/7 230V a.c. 50Hz
- Box total dimensions 110x88x50 mm. (WxDxH)
- Terminals' size 2.5 mm²
- Pulse time minimum 500mSec .
- Satisfies all the technical regulations applicable to the product within the scope of Council Directives 73/23/EEC:

EN 55014-1(2000)+ EN55014-1/A1 (2001)+EN55014-1/A2 (2002)
 EN61000-3-2 (2000)
 EN61000-3-3 (1995)+ EN61000-3-3/A1 (2001)
 EN55014-2(1997)+ EN55014-2/A1 (2001)
 EN60335-1 EN60335-2



LOW VOLTAGE CONTACT INTERFACE

Dimension: 88x50x110 mm (WxDxH)

EUROSCREEN S.r.l.

Via Stiria, 45/16 - 33100 Udine - Italy

Tel. +39 0432 522755

info@screenint.com

www.screenint.com



Euroscreen S.r.l. has reserved the right to modify its products at anytime without obligation of notice, in order to improve their performances.